

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of:)
)
Nishi et al.)
)
Serial No.:)
)
Filed: Herewith)
)
For: EL Display Device)
)
Examiner:)
)
Art Unit:)

"Express Mail" Mailing Label No. EV 321707764

Date of Deposit June 23, 2003

I hereby certify that this correspondence is being deposited with the United States Postal Service "Express Mail Post Office to Addressee" service under 37 CFR1.10 on the date indicated above and is addressed to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450

Name: Yue X. Ruan
(typed or printed)

Signature Yue X. Ruan

Mail Stop Patent Application
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

PRELIMINARY AMENDMENT A

Prior to examination and calculation of fees, please enter the following amendment in the above-identified application:

IN THE CLAIMS:

Cancel Claims 1-36.

Please add the following new claims:

37.(New) A method of manufacturing a display device comprising:

forming a semiconductor layer, a gate insulating film, and a gate electrode over a substrate;

forming an insulating film over the gate electrode and the semiconductor layer;

forming a pixel electrode on the insulating film, wherein the pixel electrode is electrically connected to the semiconductor layer;

forming an EL layer over the pixel electrode;

forming an electrode over the pixel electrode; and
forming a metal film on a portion of the electrode.

38.(New) A method of manufacturing a display device according to claim 37, wherein the electrode comprises a compound of indium oxide and tin oxide.

39.(New) A method of manufacturing a display device according to claim 37, wherein the pixel electrode comprises aluminum.

40.(New) A method of manufacturing a display device according to claim 37, wherein the gate electrode is formed over the semiconductor layer.

41.(New) A method of manufacturing a display device according to claim 37, wherein the metal film comprises a lamination of titanium and aluminum.

42.(New) A method of manufacturing a display device according to claim 37, wherein the display device is an EL display device.

43.(New) A method of manufacturing a display device according to claim 37, wherein the display device is incorporated in at least one selected from the group consisting of a video camera, a head mount display, an image reproduction apparatus, a portable computer, a personal computer, a car navigation system, a mobile telephone, and a car audio equipment.

44.(New) A method of manufacturing a display device comprising:

forming a semiconductor layer, a gate insulating film, and a gate electrode over a substrate;
forming an insulating film over the gate electrode and the semiconductor layer;
forming a pixel electrode on the insulating film, wherein the pixel electrode is electrically connected to the semiconductor layer;
forming an EL layer over the pixel electrode;
forming an anode over the pixel electrode; and
forming a metal film on a portion of the electrode.

45.(New) A method of manufacturing a display device according to claim 44, wherein the anode comprises a compound of indium oxide and tin oxide.

46.(New) A method of manufacturing a display device according to claim 44, wherein the pixel electrode comprises aluminum.

47.(New) A method of manufacturing a display device according to claim 44, wherein the gate electrode is formed over the semiconductor layer.

48.(New) A method of manufacturing a display device according to claim 44, wherein the metal film comprises a lamination of titanium and aluminum.

49.(New) A method of manufacturing a display device according to claim 44, wherein the display device is an EL display device.

50.(New) A method of manufacturing a display device according to claim 44, wherein the

display device is incorporated in at least one selected from the group consisting of a video camera, a head mount display, an image reproduction apparatus, a portable computer, a personal computer, a car navigation system, a mobile telephone, and a car audio equipment.

51.(New) A method of manufacturing a display device comprising:
forming a semiconductor layer, a gate insulating film, and a gate electrode over a substrate;
forming an insulating film over the gate electrode and the semiconductor layer;
forming a pixel electrode on the insulating film, wherein the pixel electrode is electrically connected to the semiconductor layer;
forming an EL layer over the pixel electrode;
forming an electrode over the pixel electrode;
forming a metal film on the electrode; and
etching the metal film so as to be formed on a portion of the electrode.

52.(New) A method of manufacturing a display device according to claim 51, wherein the electrode comprises a compound of indium oxide and tin oxide.

53.(New) A method of manufacturing a display device according to claim 51, wherein the pixel electrode comprises aluminum.

54.(New) A method of manufacturing a display device according to claim 51, wherein the gate electrode is formed over the semiconductor layer.

55.(New) A method of manufacturing a display device according to claim 51, wherein the

metal film comprises a lamination of titanium and aluminum.

56.(New) A method of manufacturing a display device according to claim 51, wherein the display device is an EL display device.

57.(New) A method of manufacturing a display device according to claim 51, wherein the display device is incorporated in at least one selected from the group consisting of a video camera, a head mount display, an image reproduction apparatus, a portable computer, a personal computer, a car navigation system, a mobile telephone, and a car audio equipment.

58.(New) A method of manufacturing a display device comprising:
forming a semiconductor layer, a gate insulating film, and a gate electrode over a substrate;
forming an insulating film over the gate electrode and the semiconductor layer;
forming a pixel electrode on the insulating film, wherein the pixel electrode is electrically connected to the semiconductor layer;
forming an EL layer over the pixel electrode;
forming an electrode over the pixel electrode; and
forming a metal film on an edge of the electrode.

59.(New) A method of manufacturing a display device according to claim 58, wherein the electrode comprises a compound of indium oxide and tin oxide.

60.(New) A method of manufacturing a display device according to claim 58, wherein the pixel electrode comprises aluminum.

61.(New) A method of manufacturing a display device according to claim 58, wherein the gate electrode is formed over the semiconductor layer.

62.(New) A method of manufacturing a display device according to claim 58, wherein the metal film comprises a lamination of titanium and aluminum.

63.(New) A method of manufacturing a display device according to claim 58, wherein the display device is an EL display device.

64.(New) A method of manufacturing a display device according to claim 58, wherein the display device is incorporated in at least one selected from the group consisting of a video camera, a head mount display, an image reproduction apparatus, a portable computer, a personal computer, a car navigation system, a mobile telephone, and a car audio equipment.

65.(New) A method of manufacturing a display device comprising:
forming a semiconductor layer, a gate insulating film, and a gate electrode over a substrate;
forming an insulating film over the gate electrode and the semiconductor layer;
forming a pixel electrode on the insulating film, wherein the pixel electrode is electrically connected to the semiconductor layer;
forming an EL layer over the pixel electrode;
forming an anode over the pixel electrode; and
forming a metal film on an edge of the electrode.

66.(New) A method of manufacturing a display device according to claim 65, wherein the anode comprises a compound of indium oxide and tin oxide.

67.(New) A method of manufacturing a display device according to claim 65, wherein the pixel electrode comprises aluminum.

68.(New) A method of manufacturing a display device according to claim 65, wherein the gate electrode is formed over the semiconductor layer.

69.(New) A method of manufacturing a display device according to claim 65, wherein the metal film comprises a lamination of titanium and aluminum.

70.(New) A method of manufacturing a display device according to claim 65, wherein the display device is an EL display device.

71.(New) A method of manufacturing a display device according to claim 65, wherein the display device is incorporated in at least one selected from the group consisting of a video camera, a head mount display, an image reproduction apparatus, a portable computer, a personal computer, a car navigation system, a mobile telephone, and a car audio equipment.

72.(New) A method of manufacturing a display device comprising:

forming a semiconductor layer, a gate insulating film, and a gate electrode over a substrate;

forming an insulating film over the gate electrode and the semiconductor layer;

forming a pixel electrode on the insulating film, wherein the pixel electrode is electrically

connected to the semiconductor layer;

forming an EL layer over the pixel electrode;

forming an electrode over the pixel electrode;

forming a metal film on the electrode; and

etching the metal film so as to be formed on an edge of the electrode.

73.(New) A method of manufacturing a display device according to claim 72, wherein the electrode comprises a compound of indium oxide and tin oxide.

74.(New) A method of manufacturing a display device according to claim 72, wherein the pixel electrode comprises aluminum.

75.(New) A method of manufacturing a display device according to claim 72, wherein the gate electrode is formed over the semiconductor layer.

76.(New) A method of manufacturing a display device according to claim 72, wherein the metal film comprises a lamination of titanium and aluminum.

77.(New) A method of manufacturing a display device according to claim 72, wherein the display device is an EL display device.

78.(New) A method of manufacturing a display device according to claim 72, wherein the display device is incorporated in at least one selected from the group consisting of a video camera, a